



XVGB4SW

Tower Light - RAGB - 24V - LED - W.Buzzer - Base mounting



Main

Range of product	Harmony XVG
Product or component type	Complete pre-wired monolithic tower light
Beacon or indicator bank unit type	4 illuminated units
Material	PC (UL94 V-2) globe ABS (UL94HB) tube body Aluminium tube
Mounting diameter	60 mm
Component name	XVG
Device mounting	Base mounting
Light source	LED steady blue LED steady green LED steady red LED steady amber
Light block color	Red/amber/green/blue
Indicator bank base type	Base with integrated buzzer

Complementary

[Us] rated supply voltage	24 V AC/DC
Cable cross section	0.33 mm ²
[Uimp] rated impulse withstand voltage	0.5 kV
Current consumption	207 mA
Noise level	85 dB
Power consumption	4.8 W
Fundamental frequency	2.64 kHz
Product weight	0.29 kg

Environment

Product certifications	CE
Ambient air temperature for storage	-35...70 °C
Ambient air temperature for operation	-10...50 °C
IP degree of protection	IP42

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0814 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold