

## Schneider Electric / Square D DU322RB 3 Wire Non-Fusible General Duty Disconnect Switch; 60 Amp, 240 Volt, 3 Pole



Vendor: **Schneider Electric / Square D**

Cat #: **DU322RB**

Part#: **110849**

SKU: **17656**

UPC: **785901491767**

### Schneider Electric / Square D DU322RB 3 Wire Non-Fusible General Duty Disconnect Switch; 60 Amp, 240 Volt, 3 Pole

#### PRODUCT DETAILS

- Size: 7.750 Inch Width x 3.750 Inch Depth x 9.630 Inch Height
- Rainproof and Sleet/Ice proof (Indoor/Outdoor)
- Horsepower rated for motor applications
- Tangential combination knockouts 30-200 Amp
- Spring reinforced plated copper fuse clips
- Insulated, bonded solid neutral assemblies (standard in fusible switches)
- Visible blades, quick-make, quick-break operating mechanism
- Cover padlock hasp and handle lock OFF

Schneider Electric / Square D 3-Pole 3-Phase General duty safety switch employs quick-make, quick-break operating mechanism for positive operation. It has power rating of 200 hp at 240 VAC that is suitable for motor applications. Switch is ideal for residential as well as commercial applications where economy is main consideration. It is suitable for lighting, air conditioning and appliances. It measures 7.750 Inch x 3.750 Inch x 9.630 Inch. It has a voltage rating of 240 VAC and current rating of 60 Amps. It accommodates 3/0 AWG - 500 kcmil size cable and #10 - #2 AWG size aluminum wire, #14 - #2 AWG copper wire. Non-fusible switch features visible blades and comes with lugs connection for convenience. The three-wire general duty switch has tangential combination knockouts. The insulated, bonded solid neutral assemblies provide durability. Switch features spring reinforced plated copper fuse clips for high conductivity. It has cover padlock hasp and handle lock OFF for easy use. It offers over-current and short circuit protection when equipped with fuses. Switch works as service equipment when used with either a factory-installed solid neutral assembly or a field-installed equipment grounding kit. Safety switch is rainproof as well as sleet/ice proof. It has NEMA 3R enclosure for protection. Safety switch is UL listed.

## PRODUCT SPECIFICATIONS

<b>Action</b>	Single Throw
<b>Amperage</b>	600 A
<b>Amperage Rating</b>	60
<b>Application</b>	Commercial, Residential
<b>Brand Name</b>	Schneider Electric / Square D
<b>Cable Size</b>	3/0 AWG to 500 Kcmil
<b>Connection</b>	Lugs
<b>Contact Configuration</b>	Single Throw
<b>Enclosure</b>	NEMA 3R
<b>Environmental Conditions</b>	Rainproof and Sleet/Ice proof (Indoor/Outdoor)
<b>GTIN</b>	00785901491767
<b>HP Rating</b>	240 Volt AC: 200 hp At 3 Phase
<b>Item</b>	Non-Fusible General Duty Disconnect Switch
<b>Length</b>	24.00
<b>Mfr/Vendor</b>	Schneider Electric / Square D
<b>Mounting</b>	Surface
<b>NEMA Rating</b>	3R
<b>Number of Poles</b>	3
<b>Number of Wires</b>	3
<b>Operation Type</b>	Manual
<b>Order Minimum</b>	1
<b>Phase</b>	3
<b>Power Rating</b>	200 Hp At 240 VAC 3 Phase
<b>ShipWeight</b>	4.78
<b>ShortDescriptionStripped</b>	Schneider-Electric-Square-D-DU322RB-3-Wire-Non
<b>Special Features</b>	Non-Fusible
<b>Standard</b>	UL Listed File Number E2875
<b>Standards</b>	UL Listed
<b>Switch Type</b>	Single Throw
<b>Type</b>	3 Wire, Indoor/Outdoor
<b>UPC</b>	785901491767
<b>Voltage</b>	240
<b>Voltage Rating</b>	240
<b>Wire Size</b>	10-2 AWG (Aluminum), 14-2 AWG (Copper)
<b>Wire Type</b>	#10 to #2 AWG(Al) - #14 to #2 AWG(Cu)
<b>description</b>	General duty safety switches are designed for residential and commercial applications where durability and economy are prime considerations. Typical loads are lighting, air conditioning, and appliances. They are suitable for use as service equipment when equipped with a factory- or field-installed neutral assembly or a field-installed service grounding kit, as applicable.
<b>feature#1</b>	Current Rating 60 Amp
<b>feature#2</b>	Height 9 5/8 Inches, Depth 3 3/4 Inches, Width 7 1/4 Inches
<b>feature#3</b>	3 Wire
<b>feature#4</b>	Series E
<b>feature#5</b>	NEMA 3R