

ECO RefLED MR16 3.6W-5.5W



Feature

- Simple retrofit replacement of low voltage halogen lamps (12V)
- Professional, high performance 3.6W and 5.5W Non-dim versions
- Warm white 2700K/ Daylight 6500K
- High colour rendering CRI 80
- Ideal for accent lighting (rooms, elevators, displays) in open/ventilated luminaires
- Wide compatibility with existing electromagnetic and some electronic halogen transformers

Benefits

- Very long life up to 25,000h
- Switching Cycles 200,000 times
- Great beam control
- Up to 89% energy saving
- Warm white like halogen
- Warm natural colour rendering
- Shape and size same as Halogen MR16, Can replace Halogen MR16 in same fitting
- Low IR and no UV radiation
- For accent and general lighting in hotels, restaurants, shops, offices and museums



SPECIFICATION

Product Description	Voltage	Color	Color in Kelvin	Wattage	Base	Equivalent Watt	Lumen	Lm/W	CRI	Candela	Beam	Life(Hrs)	Dimmable
ECO RefLED MR16 3.6W 36° 827	12V AC/DC	WarmWhite	2700K	3.6W	GU5.3	35W	250	69	80	550	36	25,000	No
ECO RefLED MR16 3.6W 36° 865	12V AC/DC	Daylight	6500K	3.6W	GU5.3	35W	290	81	80	620	36	25,000	No
ECO RefLED MR16 5.5W 36° 827	12V AC/DC	WarmWhite	2700K	5.5W	GU5.3	50W	350	64	80	750	36	25,000	No
ECO RefLED MR16 5.5W 36° 865	12V AC/DC	Daylight	6500K	5.5W	GU5.3	50W	410	75	80	860	36	25,000	No

DIMENSION

